Medical Bedpan Washers

B-0682-ST

TAG:


Bedpan Washer

Architect/Engineering Specifications:

8" concealed bypass mixing valve with brass body and polished chrome plated brass adjustable wall flanges and sleeves, polished chrome plated spout with garden hose male outlet, compression cartridges, 4-arm handles, 1/2" NPT female loose key straight stop inlets with tee handles, atmospheric vacuum breaker, wall hook, 68" reinforced PVC hose with spray valve and extended spray nozzle. Certified to ASME A112.18.1/CSA B125.1, NSF 61-section 9, NSF 372 and ASSE 1001.

Job Name Model Specified Quantity_ Variations Specified Date







Product Compliance:

- 8" concealed bypass mixing valve w/ 1/2" NPT female union inlet
- 6" tall polished chrome plated brass adjustable wall flanges & sleeves
- Polished chrome plated spout w/ garden hose male outlet
- Eterna compression cartridges

Features & Benefits:

- 4-arm handles w/ color coded indexes
- 1/2" NPT female loose key straight stop inlets w/ tee handles
- 1/2" NPT atmospheric vacuum breaker wall hook
- 68" reinforced PVC hose with spray valve and extended spray nozzle
- Material: Brass body, polished chrome plated brass adjustable flanges, vacuum breaker & wall hook and polished chrome plated metal handles

- ASME A112.18.1 / CSA B125.1
- NSF 61 Section 9
- NSF 372 (Low Lead Content)
- ASSE 1001 (VB)

Warranty: One Year (Limited)

PVC Hose: Two year (Limited)



Performance Data:

Pressure: 20 - 125 psi Temperature: 40°F - 140°F

Optional Handles

- □ 4" Wrist Action
- □ Lever
- □ 4-Arm (Standard)


- □ Quarter Turn Cerama
- ☐ Eterna (Standard)
- □ Quarter turn Eterna














Optional Cartridges

Date: 04/10/15