

(General Model Name: EFX600.010.0000 CP SENSOR FAUCET)

CODE NUMBER

3324487

DESCRIPTION

Hardwired Less Plug Power Supply, Mixer Not Included, Polished Chrome Finish, 0.5 gpm, Multi-Laminar Spray, Capacitance Sensor, BASYS® Hardwired-Powered Deck-Mounted Low Integrated Base Body Faucet.

DETAILS

Flow Rate: 0.5 gpm (2 Lpm) (0.5GPM)
Spray Type: Multi-Laminar (MLM)
Sensor Type: Capacitance (CAP)
Mounting Type: Single Hole

Power Supply: Hardwired Less Plug (HLP)
Temperature Mixer: Mixer Not Included

Finish: Polished Chrome (CP)
Factory Default Timeout: 10s
Factory Default GPC: 0.083

FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-CastMetal Hand Washing Faucet with the following features:

- Solenoid housed in removable carrier that includes supply strainer
- Integral water supply shut off
- Supply strainer serviceable from above deck
- Vandal resistant spray insert, key housed inside faucet body
- All electronics sealed to IP-77
- Gold plated electrical contacts
- Above deck individual diagnostic indicators for battery life, solenoid condition, and power-up mode
- Flexible, high pressure supply hoses, 3/8" compression connections
- Bi-stable magnetic solenoid
- Four (4) "AA" alkaline batteries
- Double infrared sensors with automatic setting feature
- Integral 4-inch base
- Includes all mounting hardware
- Line Purge mode, eliminates stagnant water
- Standard Bowed Crown
- Buy America Act (BAA) Compliant

VIDEOS




BASYS® Faucet Installation and Features

DOWNLOADS

- EFX 3Xx/6Xx Active IR Installation Instructions
- EFX 3Xx/6Xx Active IR (SP) Installation Instructions
- EFX 3Xx/6Xx Capacitance Installation Instructions
- EFX 3Xx/6Xx (SP) Installation Instructions
- Trim Plates Repair and Maintenance Guide
- IR FAQs Repair and Maintenance Guide





COMPLIANCES & CERTIFICATIONS















(ADA Compliant, UL Certified, CEC Compliant, CalGreen Compliant, GPC 0.25 or less, BAA Compliant, cUPC Low Lead Compliant)

NOTES

All information contained within this document subject to change without notice.

Looking for other variations of the EFX-600 product? View the general spec sheet with all options.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.

WARRANTY

3 Year



(General Model Name: EFX600.010.0000 CP SENSOR FAUCET)

- IR FAQs SP Repair and Maintenance Guide
- EFX-6XX Repair and Maintenance Guide
- EFX-6XX IR Repair and Maintenance Guide
- Additional Downloads

*One (1) faucet per battery pack

ROUGH-IN

EFX-600.X0X.0000. Faucet with hot and cold water supply **SPOUT** 1-3/16" 930 MM) 1 1/2" (38 MM) MAX. DECK THICKNESS MIN. DIA. HOLE REQUIRED RETAINER -NUT ADAPTER w/28" CORD 13" (330 mm) BACK-UP LONG FLEX HOSE BATTERY PACK* IF A CONNECTION TO SEPARATE HOT TEMPERED AND COLD WATER SUPPLIES IS DESIRED, SUPPLY THAN A BAK-CHEK TEE FITTING MUST BE USED PRIOR TO CONNECTING TO THE FAUCET.

