T&S BRASS AND BRONZE WORKS 2 Saddleback Cove / P.O. Box 1088 Travelers Rest, SC 29690	EC-TMV
Travelers Rest, SC: 800-476-4103 • Simi Valley, CA: 800-423-0150 • Fax: 864-834-351	8 • www.tsbrass.com
4 1/8" [105mm] Customer/A Contractor	Space for Architect/Engineer Approval Date cifiedQuantity Wholesaler ngineer
Mixed Water to Fixture 1/2" NPSM Male (3 Places) Integral Check Valves Built into Hot and Cold Inlet Check Valve Filter Screens (Included) Hot Inlet Cold Inlet	4 5/8" [118mm]
Exceeding Customer's Maximum To Set Point. Valve is Factory Pre-set to Deliver I Temperature of Approximately 100	emperature Mixed Water
Performance Rating: Minimum Flow Rate: 0.5 GPM Pressure Drop at Minimum Flow Rate: 0.5 psi Maximum Pressure: 125 psi Hot Water Inlet Temperature Range: 120~180°F (49~82°C) Outlet Temperature Range: 80~120°F (27~49°C) Outlet Temperature Factory Setting: Approx. 100°F (38°C)	Product Compliance:
Product Specifications: Thermostatic Mixing Valve with 1/2" NPSM Male Fittings	Product Compliance: NSF 61 - Section 9 NSF 372 (Low Lead Content) ASSE 1070 (TMV)
Drawn: DHL Checked: GEF Approved: JHB Date: 02/16/1	5 Scale: 1:2 Sheet: 1 of 1