

Unbreakable stainless steel mirror with No. 8 architectural bright finish:

☐ Model 748-XXXX (Specify width and height)

Product Materials

MIRROR: 20 gauge stainless steel, polished to No. 8 architectural bright finish. Stretcher leveled for uniformity. Very bright — excellent reflectivity, very slight polish grain. ¼" return conceals backing.

BACKING: tempered Masonite bonded to mirror with adhesive.

Stainless steel mirrors will differ in optic quality from glass mirrors.

Installation

Verify all rough-in dimensions prior to installation. Secure to wall with tamper-resistant mounting screws (included) at holes provided. Provide in-wall backing at mounting screw locations.

Guide Specification

Mirror shall be fabricated of 20 gauge stainless steel with No. 8 architectural finish. Unit shall have $\frac{1}{4}$ " return to conceal $\frac{1}{4}$ " tempered Masonite backing bonded to mirror with adhesive.

Stainless Steel Mirror shall be Bradley Model 748-_____" W x_____" H (specify width and height).

Model 748 series stainless steel mirrors can be fabricated to a maximum size of 47% W x 72"H.

In larger sizes, these units are subject to distortion and/or "oil canning" for which Bradley Corporation cannot accept responsibility.

ADA Compliant

Consult local and national accessibility codes for proper installation guidelines.

Conformity and compliance to local and national codes is the responsibility of the installer

Dim. "A" Key Surface:	For Dim. "A"	Bottom of Unit
Mirror's bottom edge of the reflecting surface to finished floor	40" (1016mm)	40" (1016mm)
	37" (940mm)	37" (940mm)
	34" (864mm)	34" (864mm)
Rough wall opening:		
Surface Mount:	No rough wall opening, see overall dimensions	

(4) Mounting Holes "H" 3/4" (19mm) Тур. Dim. "A" to finished floor

Washroom Accessories Document No. 8740