

Grout HD penetrates and quickly removes ground in grime from tile, grout lines, leaving behind a bright and revitalized surface.

Grout HD utilizes cutting edge technology to provide a product free of harsh chemicals like strong acids and caustic soda, allowing it to be safe on skin and the environment.

Effective on

Dirt •Grease •Wax Mildew Soap Scum

SUGGESTED DILUTIONS: Dilutes with water.

Apply with a mop or sprayer. Let stand for 10 minutes and agitate with a deck brush or scrub pad. Rinse with clean water.

TERRAZZO - CERAMIC TILE - TRAVERTINE - CONCRETE

MEDIUM SOIL:

Add 8-10 fl. oz. (237-296 mL) of **Grout HD** to 1 gallon (3.785 L) of water.

HEAVY SOIL:

Add 16 fl. oz. (473 mL) of **Grout HD** to 1 gallon (3.785 L) of water.

SHOCK TREATMENT:

Add 32 fl. oz. (946 mL) of **Grout HD** to 1 gallon (3.785 L) of water.

FOR ALL MARBLE AND OTHER SOFT STONE

Add 2 fl. oz. (30 mL) of **Grout HD** to 1 gallon (3.785 L) of water. NOTE: Using Grout HD at a stronger dilution is not recommended, may cause etching.

DILUCIONES SUGERIDAS:

Dilua con agua. Aplicar con un trapeador o rociador. Dejar reposar durante 10 minutos y agitar con un cepillo de cubierta o matorral. Énjuague con agua limpia.

TERRAZZO - AZULEJO CERÁMICO - TRAVERTINE - HORMIGÓN

SUELO MEDIO: Añadir 237 - 296 ml de lechada HD a 3,785 l de agua. SUELO PESADO: Añada 473 ml de lechada HD a 3,785 l de agua. TRATAMIENTO DE CHOQUE: Añada 946 ml de lechada HD a 3,785 l de agua.

PARA TODOS LOS MÁRMOLES Y OTRAS PIEDRAS SUAVES

Añadir 30 ml de lechada HD a 3,785 l de agua.

NOTA: No se recomienda utilizar Grout HD con una dilución más fuerte, ya que puede causar grabado.





Nilodor, Inc.

10966 Industrial Parkway, N.W. P.O. Box 660 Bolivar, OH 44612-0660 U.S.A. 1-800-443-4321 or (330) 874-1017 FAX (330) 874-3366 www.nilodor.com

Odor Control & Facility Care Solutions







SUPERMARKETS SCHOOLS

NURSING HOMES RESTAURANTS

CASINOS HOTEL/MOTEL

HOSPITALS WAREHOUSES

Grout HD Cleaner & Revitalizer

An inhibited hydrochloric acid works synergistically with degreasing surfactants to lift and remove ground in soils.

Grout HD contains a pair of heavy duty degreasing surfactants that work together with an inhibited hydrochloric acid to rejuvenate tile to its original appearance. The two surfactants work together to provide fast penetration and removal of heavy oil, grease, wax and particulate soils from grout.

- •Also effective on glass, concrete, and other hard surfaces.
- •Can use at a lower dilution than common hard surface cleaners.
- •Safe and User Friendly



Test results from Grout HD Cleaner & Revitalizer

- A Grout before Grout HD treatment
- **B** 5 minute dwell time with Grout HD after agitation
- **C** 10 minute dwell time with Grout HD after agitation
- **D-** 15 minute dwell time with Grout HD after agitation



Grout HD Key Selling Points

Grout HD uses an inhibited hydrochloric acid that works synergistically with degreasing surfactants, to rejuvenate tile and grout to its original appearance.

- Phosphoric acid, caustic soda and bleach FREE
- Non corrosive to skin
- Low VOC and does not create harmful fumes
- Non abrasive on fragile surfaces
- Rinses clean at any water temperature
- · No noxious odor
- **Grout HD's** primary degreasing surfactant was originally designed for use on cleaning and degreasing aircraft engines.
- Provides fast wetting/penetration, rinses clean at any water temperature.
- Is also effective as a tub and tile cleaner, toilet bowl cleaner, scale remover, rust stain remover, and a vinyl and aluminum siding cleaner.





Nilodor, Inc.

10966 Industrial Parkway, N.W. P.O. Box 660 Bolivar, OH 44612-0660 U.S.A. 1-800-443-4321 or (330) 874-1017 FAX (330) 874-3366 www.nilodor.com

Odor Control & Facility Care Solutions







