ertified by Nilodo Spray Paint, Permanent Marker, **Oil & Water Based Enamel** -Brick Stainless Steel -Stone -Fiberglass -Concrete -Tile la pintura de aerosol, marcador permanente pintura al óleo, agua en la Pintura Net Contents: 32 Fl. oz. (946 ml) **Aerosol Spray Paint** Lacquers •

Quarts - 6/cs. C517-009 • R-T-U pH 5-6

Graffiti Remover is a ready to use water based paint remover. Safely breaks down the bond between paint and the surface. Removes unwanted graffiti from both hard and carpeted surfaces without harsh chemicals. Non-toxic and biodegradable.

•Brick & Tile	 Concrete 	•Stucco
•Aluminum	 Fiberglass 	•Plastic
•Formica	 Metal Signs 	•Stone
•Rock	 Stainless Steel 	



DIRECTIONS FOR USE

Shake well before using. Test on all surfaces in an inconspicuous area before using. If surface mars, dulls, discolors, fades or fiber color transfers to a white cloth, do not use. Test all plastics before using.

FOR BRICK, CONCRETE & STUCCO:

- 1. Apply to problem area, wait 3-5 minutes.
- 2. Use brush to loosen dried paint. Use hose to
- rinse off, and wipe clean with a towel.

3. For porous problem areas, use a high pressure sprayer after Step 1.

FOR HARD & SOFT SURFACES (Street Signs, Tile, Etc.):

- 1. Spray problem areas and wait for one minute.
- 2. Wipe with clean towel.
- **3.** Repeat if necessary.

Do Not Mix with Bleach or use in conjunction with any household products.





Nilodor, Inc. 10966 Industrial Parkway, N.W. P.O. Box 660 Bolivar, OH 44612-0660 U.S.A. 1-800-443-4321 or (330) 874-1017 FAX (330) 874-3366 www.nilodor.com

Odor Control & Facility Care Solutions