

CODE NUMBER

3400219

DESCRIPTION

0.25 gpf, Filtered, Rough Brass Finish, Black Wall Plate Finish, Single Flush, Integrated Control Stop, 3.25-4.25 L Dimension, Adjustable Flush Connection Outlet Tube, ADA Compliant Push Button, Short V500A & Adjustable Flush Connection Vacuum Breaker, Front Accessible Wall Box, CX Concealed Manual Urinal Flushometer.

DETAILS

Flush Volume: 0.25 gpf (0.9 Lpf)
Finish: Rough Brass (RB)
Wall Plate Finish: Black (BLK)

Valve: Piston Bypass: Filtered

• Valve Body Material: Semi-red Brass

Fixture Type: UrinalFixture Connection: Rear

• Rough-In Dimension: 12 5/8" (321mm)

Spud Coupling: ³/₄" (19mm)
Supply Pipe: ³/₄" (19mm)

• L Dimension: 3 1/4" - 4 1/4" (83 - 108mm)

Wall Box: Front AccessiblePush Button: ADA CompliantControl Stop: Integrated

• Vacuum Breaker: Short V500A & Adjustable Flush Connection

• Outlet Tube: Adjustable Flush Connection

FEATURES

- Fixed volume piston with filtered O-ring bypass
- Front access wall plate requires no rear access plumbing chase
- ADA compliant push button
- Vandal resistant wall plate
- Adjustable flush connection

VIDEOS

- CX Flushometer Product Video
- CX Flushometer Manual Installation
- CX Flushometer Manual Vacuum Service
- CX Flushometer Manual Piston Service
- CX Flushometer Product Video (Spanish)



RECOMMENDED SPECIFICATION

Valve shall be concealed with front access plate smaller than $10^{\prime\prime}$ x $10^{\prime\prime}$ and shall have integrated control stop. Valve body shall be in compliance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037.

VALVE OPERATING PRESSURE (FLOWING)

20–80 PSI (138–552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

DOWNLOADS

- CX 158 / 198 Installation Instructions
- CX 158 / 198 Repair and Maintenance Guide
- Additional Downloads

NOTES

All information contained within this document subject to change without notice.

Looking for other variations of the CX 198 product? View the general spec sheet with all options.

Find a compatible urinal for this flushometer. Find a compatible water closet for this flushometer.

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com



ROUGH-IN

