

BASYS® SENSOR FAUCET EFX-200-8-PLG-CP-0.5GPM-MLM-IR-FCT

(General Model Name: EFX200.000.0210)

CODE NUMBER

3324344

DESCRIPTION

8" Trim Plate, Plug Adapter Power Supply, Mixer Not Included, Polished Chrome Finish, 0.5 gpm, Multi-Laminar Spray, Infrared Sensor, BASYS® Hardwired-Powered Deck-Mounted Mid Body Faucet.

DETAILS

Flow Rate: 0.5 gpm (2 Lpm) (0.5GPM)
 Spray Type: Multi-Laminar (MLM)

Sensor Type: Infrared (IR)
Mounting Type: Single Hole
Trim Plate: 8" (203mm) (8)
Power Supply: Plug Adapter (PLG)

Temperature Mixer: Mixer Not Included

Finish: Polished Chrome (CP)
 Factory Default Timeout: 10s
 Factory Default GPC: 0.083

FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-CastMetal Hand Washing Faucet with the following features:

- · One tool service
- All wetted components to be stainless steel, engineered thermoplastic, EPDM, and copper or copper alloy
- Solenoid housed in removable carrier that includes supply strainer
- Integral water supply shut off
- Supply strainer serviceable from above deck
- Vandal resistant spray insert, key housed inside faucet body
- All electronics sealed to IP-163
- Gold plated electrical contacts
- Above deck individual diagnostic indicators for battery life, solenoid condition, and power up mode
- Flexible, high pressure supply hoses, 3/8" compression connections
- Bi-stable magnetic solenoid
- Four (4) "AA" alkaline batteries
- Double infrared sensors with automatic setting feature Includes all mounting hardware
- Line purge mode, eliminates stagnant water
- Adjustable time-outs
- Standard Bowed Crown

VIDEOS


BASYS® Faucet Installation and Features

BASYS® Faucet Installation Mid Height Model

DOWNLOADS

- EFX 1Xx/2Xx Installation Instructions
- EFX 1Xx/2Xx (SP) Installation Instructions
- EFX 1Xx/2Xx Caddy Replacement Installation Instructions





COMPLIANCES & CERTIFICATIONS











(ADA Compliant, UL Certified, CEC Compliant, CalGreen Compliant, GPC 0.25 or less, cUPC Low Lead Compliant)

NOTES

All information contained within this document subject to change without notice.

Looking for other variations of the EFX-200 product? View the general spec sheet with all options.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.



BASYS® SENSOR FAUCET EFX-200-8-PLG-CP-0.5GPM-MLM-IR-FCT

(General Model Name: EFX200.000.0210)

- Trim Plates Repair and Maintenance Guide
- IR FAQs Repair and Maintenance Guide
- IR FAQs SP Repair and Maintenance Guide
- EFX-2XX Repair and Maintenance Guide
- Additional Downloads

ROUGH-IN

EFX-200.00X.0X1X Faucet with Single Line Water Supply

ADAPTER W
28" CORD

I3" (330 mm)

NUT

ADAPTER W
28" CORD

I" (300 mm)

MAX DECK
THICKNESS


NUT

LONG FLEX HOSE

If a connection to separate hot and cold water supplies is desired, then a Bak-Chek* tee fitting (not supplied) must be used prior to connecting to the faucet.

EFX-200.50X.0X1X Faucet

with Hot & Cold Water Supply



WARRANTY

3 Year

Electrical Connection for up to 6 Faucets

Can combine up to six (6) faucets using one adapter

