EFX-200-4-PLG-BDT-CP-1.5GPM-MLM-IR-FCT

(General Model Name: EFX200.203.0110)

CODE NUMBER

3324450

DESCRIPTION

4" Trim Plate, Plug Adapter Power Supply, Below Deck Thermostatic Mixing Valve, Polished Chrome Finish, 1.5 gpm, Multi-Laminar Spray, Infrared Sensor, BASYS® Hardwired-Powered Deck-Mounted Mid Body Faucet.

DETAILS

Flow Rate: 1.5 gpm (6 Lpm) (1.5GPM)
Spray Type: Multi-Laminar (MLM)

Sensor Type: Infrared (IR)
Mounting Type: Single Hole
Trim Plate: 4" (102mm) (4)
Power Supply: Plug Adapter (PLG)

• Temperature Mixer: Below Deck Thermostatic Mixing Valve (BDT)

Finish: Polished Chrome (CP)
Factory Default Timeout: 10s
Factory Default GPC: 0.75

FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-CastMetal Hand Washing Faucet with the following features:

- · One tool service
- All wetted components to be stainless steel, engineered thermoplastic, EPDM, and copper or copper alloy
- Solenoid housed in removable carrier that includes supply strainer
- Integral water supply shut off
- Supply strainer serviceable from above deck
- Vandal resistant spray insert, key housed inside faucet body
- All electronics sealed to IP-138
- Gold plated electrical contacts
- Above deck individual diagnostic indicators for battery life, solenoid condition, and power up mode
- Flexible, high pressure supply hoses, 3/8" compression connections
- Bi-stable magnetic solenoid
- Four (4) "AA" alkaline batteries
- Double infrared sensors with automatic setting feature Includes all mounting hardware
- Line purge mode, eliminates stagnant water
- Adjustable time-outs
- Standard Bowed Crown

VIDEOS


BASYS® Faucet Installation and Features

BASYS® Faucet Installation Mid Height Model

DOWNLOADS

- EFX 1Xx/2Xx Installation Instructions
- EFX 1Xx/2Xx (SP) Installation Instructions





COMPLIANCES & CERTIFICATIONS







(ADA Compliant, UL Certified, CEC Compliant, cUPC Low Lead Compliant)

NOTES

All information contained within this document subject to change without notice.

Looking for other variations of the EFX-200 product? View the general spec sheet with all options.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.



BASYS® SENSOR FAUCET EFX-200-4-PLG-BDT-CP-1.5GPM-MLM-IR-FCT

(General Model Name: EFX200.203.0110)

- EFX 1Xx/2Xx Caddy Replacement Installation Instructions
- Trim Plates Repair and Maintenance Guide
- IR FAQs Repair and Maintenance Guide
- IR FAQs SP Repair and Maintenance Guide
- EFX-2XX Repair and Maintenance Guide
- Additional Downloads

ROUGH-IN

EFX-200.00X.0X1X Faucet with Single Line Water Supply

ADAPTER W/
28" CORD

In 37 (330 mm)

NUT

ADAPTER W/
28" CORD

In 37 (330 mm)

LONG FLEX HOSE

If a connection to separate hot and cold water supplies is desired, then a Bak-Chek* lee fitting (not supplied) must be used prior to connecting to the faucet.

EFX-200.50X.0X1X Faucet with Hot & Cold Water Supply

SPOUT

1-3/16" (30 mm)

MIN DIA HOLE
REQUIRED

RETAINER

ADAPTER W

28" CORD

13" (330 mm)

LONG FLEX HOSE

COLD

HOT SUPPLY

WARRANTY

3 Year

Electrical Connection for up to 6 Faucets

Can combine up to six (6) faucets using one adapter

