

(General Model Name: EFX200.502.0110 CP SENSOR FAUCET)

#### **CODE NUMBER**

3324459

#### **DESCRIPTION**

4" Trim Plate, Plug Adapter Power Supply, Integrated Side Mixer, Polished Chrome Finish, 1.5 gpm, Aerated Spray, Infrared Sensor, BASYS® Hardwired-Powered Deck-Mounted Mid Body Faucet.

#### **DETAILS**

• Flow Rate: 1.5 gpm (6 Lpm) (1.5GPM)

Spray Type: Aerated (AER)
Sensor Type: Infrared (IR)
Mounting Type: Single Hole
Trim Plate: 4" (102mm) (4)

• Power Supply: Plug Adapter (PLG)

• Temperature Mixer: Integrated Side Mixer (ISM)

Finish: Polished Chrome (CP)
 Factory Default Timeout: 10s
 Factory Default GPC: 0.75

#### **FEATURES**

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-CastMetal Hand Washing Faucet with the following features:

- · One tool service
- All wetted components to be stainless steel, engineered thermoplastic, EPDM, and copper or copper alloy
- Solenoid housed in removable carrier that includes supply strainer
- Integral water supply shut off
- Supply strainer serviceable from above deck
- Vandal resistant spray insert, key housed inside faucet body
- All electronics sealed to IP-150
- Gold plated electrical contacts
- Above deck individual diagnostic indicators for battery life, solenoid condition, and power up mode
- Flexible, high pressure supply hoses, 3/8" compression connections
- Bi-stable magnetic solenoid
- Four (4) "AA" alkaline batteries
- Double infrared sensors with automatic setting feature Includes all mounting hardware
- Line purge mode, eliminates stagnant water
- Adjustable time-outs
- Standard Bowed Crown

#### **VIDEOS**


BASYS® Faucet Installation and Features

BASYS® Faucet Installation Mid Height Model

#### **DOWNLOADS**

- EFX 1Xx/2Xx Installation Instructions
- EFX 1Xx/2Xx (SP) Installation Instructions
- EFX 1Xx/2Xx Caddy Replacement Installation Instructions





#### **COMPLIANCES & CERTIFICATIONS**







(ADA Compliant, UL Certified, CEC Compliant, cUPC Low Lead Compliant)

#### **NOTES**

All information contained within this document subject to change without notice.

Looking for other variations of the EFX-200 product? View the general spec sheet with all options.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.



# BASYS® SENSOR FAUCET EFX-200-4-PLG-ISM-CP-1.5GPM-AER-IR-FCT

(General Model Name: EFX200.502.0110 CP SENSOR FAUCET)

- Trim Plates Repair and Maintenance Guide
- IR FAQs Repair and Maintenance Guide
- IR FAQs SP Repair and Maintenance Guide
- EFX-2XX Repair and Maintenance Guide
- Additional Downloads

#### **ROUGH-IN**

## **EFX-200.00X.0X1X Faucet** with Single Line Water Supply


ADAPTER W
28° CORD

I33° (30 mm)
LONG FLEX HOSE

If a connection to separate hot and cold water supplies is desired, then a Bak-Chek\* tee fitting (not supplied) must be used prior to connecting to the faucet.

### EFX-200.50X.0X1X Faucet

with Hot & Cold Water Supply



WARRANTY

3 Year

#### **Electrical Connection for up to 6 Faucets**

Can combine up to six (6) faucets using one adapter

