

## Crown® Model Flushometer

# 116-1.6

### Description

Exposed, Water Closet Flushometer for floor mounted or wall hung top spud bowls. Valve cannot be converted to exceed a low consumption flush.

### Flush Cycle

Model 116-1.6 Low Consumption (1.6 gpf/6.0 Lpf)

### Specifications

Quiet, Exposed, Piston Type, Chrome Plated Closet Flushometer with the following features:

- Fixed Volume Piston with Filtered O-ring Bypass
- ADA Compliant Metal Oscillating Non-Hold-Open Handle with Triple Seal Handle Packing
- 1" I.P.S. Screwdriver Bak-Chek® Angle Stop
- Locking Vandal Resistant Stop Cap
- Adjustable Tailpiece
- High Back Pressure Vacuum Breaker Flush Connection with One-piece Bottom Hex Coupling Nut
- Spud Coupling and Flange for 1½" Top Spud
- Sweat Solder Adapter with Cover Tube and Cast Set Screw Wall Flange
- High Copper, Low Zinc Brass Castings for Dezincification Resistance
- Valve designed to accept Low and Ultra-Low Consumption Pistons only to ensure Water Conservation
- Non-Hold-Open Handle, Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- Handle Packing, Main Seat, Stop Seat and Vacuum Breaker molded from PERMEX™ Rubber Compound for Chloramine Resistance


Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037.

### Variations

- ☒ **O** Offset Vacuum Breaker, Specify: 1" - 1½" - 2"
- ☒ **TP** Trap Primer
- ☒ **YI** Two Wall Bumpers (for open front seat without cover)
- ☒ **YJ** Split Ring Pipe Support
- ☒ **YK** Solid Ring Pipe Support

### Accessories

See Accessories Section of the Sloan catalog for details on these and other Flushometer variations.



Made In The  
**USA**



This space for Architect/Engineer approval

Job Name _____	Date _____
Model Specified _____	Quantity _____
Variations Specified _____	
Customer/Wholesaler _____	
Contractor _____	
Architect _____	

The information contained in this document is subject to change without notice.

## SLOAN

10500 SEYMOUR AVE. - FRANKLIN PARK, IL 60131

PHONE: 1-800-9-VALVE-9 - FAX: 1-800-447-8329

<http://www.sloanvalve.com>

## Air Delights

11170 SW 5TH STREET, SUITE 100 - BEAVERTON, OR 97005

PHONE: 1-800-440-5556 - FAX: 1-503-643-8224

<http://www.airdelights.com> - Customer\_Service@AirDelights.com