

Crown® Model Flushometer

120-1.6

Description

Exposed, Water Closet Flushometer for floor mounted back spud bowls. Valve cannot be converted to exceed a low consumption flush.

Flush Cycle

Model 120-1.6 Low Consumption (1.6 gpf/6.0 Lpf)

Specifications

Quiet, Exposed, Piston Type, Chrome Plated Closet Flushometer with the following features:

- Fixed Volume Piston with Filtered O-ring Bypass
- ADA Compliant Metal Oscillating Non-Hold-Open Handle with Triple Seal Handle Packing
- 1" I.P.S. Screwdriver Bak-Chek® Angle Stop
- Locking Vandal Resistant Stop Cap
- Adjustable Tailpiece
- High Back Pressure Vacuum Breaker Flush Connection with One-piece Bottom Hex Coupling Nut
- Elbow Flush Connection, Spud Coupling and Flange for 1½" Back Spud
- Sweat Solder Adapter with Cover Tube and Cast Set Screw Wall Flange
- High Copper, Low Zinc Brass Castings for Dezincification Resistance
- Valve designed to accept Low and Ultra-Low Consumption Pistons only to ensure Water Conservation
- Non-Hold-Open Handle, Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- Handle Packing, Main Seat, Stop Seat and Vacuum Breaker molded from PERMEX™ Rubber Compound for Chloramine Resistance


Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037.

Variations

- ☒ **U** 1¼" Flush Connection and Spud Coupling
- ☒ **YG** Extended Bumper on Angle Stop (for seat with cover)
- ☒ **YO** Bumper on Angle Stop (for open front seat without cover)

Accessories

See Accessories Section of the Sloan catalog for details on these and other Flushometer variations.



Made In The
USA



This space for Architect/Engineer approval

Job Name _____	Date _____
Model Specified _____	Quantity _____
Variations Specified _____	
Customer/Wholesaler _____	
Contractor _____	
Architect _____	

The information contained in this document is subject to change without notice.

SLOAN

10500 SEYMOUR AVE. - FRANKLIN PARK, IL 60131

PHONE: 1-800-9-VALVE-9; FAX: 1-800-447-8329

<http://www.sloanvalve.com>

Air Delights

11170 SW 5TH STREET, SUITE 100 - BEAVERTON, OR 97005

PHONE: 1-800-440-5556 - FAX: 1-503-643-8224

<http://www.airdelights.com> - Customer_Service@AirDelights.com