



21/4" MIN. (57 mm) 1" L.P.S. SUPPLY (DN 25 mm) CENTER LINE OF FIXTURE CENTER LINE OF WASTE FIN. FLOOR WALL

Crown 180 09-14 Copyright © 2014 SLOAN VALVE COMPANY

Crown® Model Flushometer

180-1.0

Description

Exposed, Urinal Flushometer for 11/4" top spud urinals. Valve cannot be converted to exceed a low consumption flush.

Flush Cycle

Model 180-1.0 Low Consumption (1.0 gpf/3.8 Lpf)

Specifications

Quiet, Exposed, Piston Type, Chrome Plated Urinal Flushometer with the following features:

- Fixed Volume Piston with Filtered O-ring Bypass
- ADA Compliant Metal Oscillating Non-Hold-Open Handle with Triple Seal Handle Packing
- 1" I.P.S. Screwdriver Bak-Chek® Angle Stop
- Locking Vandal Resistant Stop Cap
- Adjustable Tailpiece
- High Back Pressure Vacuum Breaker Flush Connection with One-piece Bottom Hex Coupling Nut
- Spud Coupling and Flange for 1¼" Top Spud
- Sweat Solder Adapter with Cover Tube and Cast Set Screw Wall Flange
- High Copper, Low Zinc Brass Castings for Dezincification Resistance
- Valve designed to accept Low and Ultra-Low Consumption Pistons only to ensure Water Conservation
- Non-Hold-Open Handle, Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- Handle Packing, Main Seat, Stop Seat and Vacuum Breaker molded from PERMEX™ Rubber Compound for Chloramine Resistance

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037.

Variations

■ T 1½" Flush Connection

Accessories

See Accessories Section of the Sloan catalog for details on these and other Flushometer variations.





This space for Architect/Engineer approval	
Job Name	Date
Model Specified	Quantity
Variations Specified	
Customer/Wholesaler	
Contractor	
Architect	

The information contained in this document is subject to change without notice.



10500 SEYMOUR AVE. - FRANKLIN PARK, IL 60131 PHONE: 1-800-9-VALVE-9 - FAX: 1-800-447-8329 http://www.sloanvalve.com



11170 SW 5TH STREET, SUITE 100 - BEAVERTON, OR 97005
PHONE: 1-800-440-5556 - FAX: 1-503-643-8224
http://www.airdelights.com - Customer_Service@AirDelights.com