

Crown[®] Model **Flushometer**



Description

Exposed, Urinal Flushometer for 34" top spud urinals. Valve cannot be converted to exceed a low consumption flush.

Flush Cvcle

Model 186-1.0 Low Consumption (1.0 gpf/3.8 Lpf)

Specifications

- Quiet, Exposed, Piston Type, Chrome Plated Urinal Flushometer with the following features:
- Fixed Volume Piston with Filtered O-ring Bypass
- ADA Compliant Metal Oscillating Non-Hold-Open Handle with Triple Seal Handle Packing
- 34" I.P.S. Screwdriver Bak-Chek® Angle Stop
- Locking Vandal Resistant Stop Cap
- Adjustable Tailpiece
- High Back Pressure Vacuum Breaker Flush Connection with One-piece Bottom Hex Coupling Nut
- Spud Coupling and Flange for 3/4 Top Spud
- Sweat Solder Adapter with Cover Tube and Cast Set Screw Wall Flange
- High Copper, Low Zinc Brass Castings for Dezincification Resistance


Made In The

- · Valve designed to accept Low and Ultra-Low Consumption Pistons only to ensure Water Conservation
- Non-Hold-Open Handle, Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- Handle Packing, Main Seat, Stop Seat and Vacuum Breaker molded from PERMEX™ Rubber Compound for Chloramine Resistance

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037.

Accessories

See Accessories Section of the Sloan catalog for details on these and other Flushometer variations.







10500 SEYMOUR AVE. - FRANKLIN PARK, IL 60131 PHONE: 1-800-9-VALVE-9 - FAX: 1-800-447-8329 http://www.sloanvalve.com



11170 SW 5TH STREET, SUITE 100 - BEAVERTON, OR 97005 PHONE: 1-800-440-5556 - FAX: 1-503-643-8224 http://www.airdelights.com - Customer_Service@AirDelights.com