



Naval[®] Model Flushometer

122 122-1.6

- ▶ **Description**
Exposed Water Closet Flushometer for floor mounted back spud bowls. Especially suited for harsh water conditions.
- ▶ **Flush Cycle**
 - Model 122 (factory set at 3.5 gpf/13.2 Lpf)
 - Model 122-1.6 (factory set at 1.6 gpf/6.0 Lpf)
 Valve Adjustment Range: 1.5 gpf/5.7 Lpf to 7.0 gpf/26.5 Lpf
- ▶ **Specifications**
Quiet, Exposed, Adjustable Piston Type, Chrome Plated Closet Flushometer with the following features:
 - ADA Compliant Metal Oscillating Non-Hold-Open Handle
 - Self-cleaning Xpelor[®] Bypass
 - 1" I.P.S. Screwdriver Bak-Chek™ Angle Stop
 - Vandal Resistant Stop Cap
 - Adjustable Tailpiece
 - Vacuum Breaker Flush Connection
 - Spud Coupling and Flange for 1½" Back Spud
 - Stamped Wall Flange
 - Ultra High Copper, Low Zinc Brass Castings for Dezincification and Salt Water Resistance
 - Handle Packing, Stop Seat and Vacuum Breaker to be Molded from PERMEX™ Rubber Compound for Chloramine Resistance

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037, ANSI/ASME 112.19.6, and Military Specification V-29193.

- ▶ **Variations**
 - GJ** Ground Joint Stop and Tailpiece
 - U** 1¼" Flush Connection and Spud Coupling
 - XYV** Less Vacuum Breaker
 - YB** Sweat Solder Adapter Kit
 - YBYC** Sweat Solder Adapter & Cast Set Screw Wall Flange
 - YI** Two Wall Bumpers (for open front seat without cover)

NOTE: Bak-Chek™ Angle Stop available with 1" Whitworth Thread (please specify).
Ground Joint Stop (GJ) recommended for salt water applications.
Vacuum Breaker usually not required when used with non-potable water (specify XYV Variation).

See Accessories Section of the Sloan catalog for details on these and other Flushometer variations.



Made in the U.S.A.

This space for Architect/Engineer approval

The information contained in this document is subject to change without notice.

