



Regal® 186-0.5 XL Flushometer



Description

Exposed Urinal Flushometer, for 3/4" top spud urinals.

Flush Cycle

☑ Model 186-0.5 High Efficiency (0.5 gpf/1.9 Lpf)

Specifications

Quiet, Exposed, Diaphragm Type, Chrome Plated Urinal Flushometer with the following features:

- ADA Compliant Metal Oscillating Non-Hold-Open Handle
- 3/4" I.P.S. Screwdriver Bak-Chek Angle Stop
- Vandal Resistant Stop Cap
- Sweat Solder Adapter with Cover Tube
- Cast Set Screw Wall Flange
- Adjustable Tailpiece
- Cast Wall Flange with Set Screw
- Vacuum Breaker Flush Connection
- Spud Coupling and Spud Flange for 3/4" Top Spud
- High Copper, Low Zinc Brass Castings for Dezincification Resistance
- Non-Hold-Open Handle and No External Volume Adjustment to Ensure Water Conservation
- Low Consumption flush accuracy controlled by Para-Flo™ Technology
- Handle Packing, Stop Seat and Vacuum Breaker to be Molded from PERMEX Rubber Compound for Chloramine Resistance

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037.

Accessories

See Accessories Section of the Sloan catalog for details on these and other Flushometer variations.

Fixtures

Consult Sloan for Sloan brand matching fixtures.



Sloan Valve Company is buying renewable energy certificates to meet 100% of the company's purchased electricity use at its Franklin Park, Illinois facility.

This space for Architect/Engineer approval

The information contained in this document is subject to change without notice.

SLOAN

Air Delights

10500 SEYMOUR AVE. - FRANKLIN PARK, IL 60131

11170 SW 5TH STREET, SUITE 100 - BEAVERTON, OR 97005

PHONE: 1-800-9-VALVE-9 - FAX: 1-800-447-8329

PHONE: 1-800-440-5556 - FAX: 1-503-643-8224

<http://www.sloanvalve.com>

<http://www.airdelights.com> - Customer_Service@AirDelights.com