

For Residential and Commercial Applications

Job Name _____

Contractor _____

Job Location _____

Approval _____

Engineer _____

Contractor's P.O. No. _____

Approval _____

Representative _____

Brass CrimpRing™ & CinchClamp™ Couplings

Brass CrimpRing™ & CinchClamp™ Couplings and Coupling Kits are used for making WaterPEX® repairs in the field, continuing a run as well as transitioning from polybutylene pipe to WaterPEX® tubing.

Specifications

System shall be plumbed using Watts WaterPEX® cross-linked polyethylene pipe, and all joints shall be made using Watts brass CrimpRing™ and/or polyalloy CrimpRing™ fittings using either the Watts copper CrimpRing™ or stainless steel CinchClamp™ crimping methods as outlined in the Watts WaterPEX® Installation Guidelines.

Installation Note

Brass Couplings must be installed in accordance with all Watts WaterPEX® installation procedures, including information provided in WaterPEX® installation manual and guidelines.

Approvals



- Manufactured in accordance with American Society for Testing and Materials (ASTM) F-877 and F-1807
- Listed by the National Sanitation Foundation to NSF Standards 14 and 61 for use in potable water systems
- Listed by NSF to be in compliant to the Uniform Plumbing Code
- Labeled B137.5 which indicates that it is compliant to the CSA Standards B137.5

* **Note:** Watts WaterPEX CinchClamp™ fittings should not be used with wrought copper PEX fittings.

Warning!

If connections must be made in temperatures below 30°F, caution must be taken to allow the WaterPEX to form a proper seal against the barb. Apply the connection slowly to ensure the PEX material conforms to the barb.



WP15
PEX x PEX CrimpRing™ Coupling



WP8S
PEX x PEX CinchClamp™ Coupling Kit
(Each kit contains 4 CinchClamps™ and 2 brass couplings)



WP16
PEX x PEX CrimpRing™ Coupling Kit
(Each kit contains 4 copper CrimpRings™ and 2 brass couplings)



WP17
PEX x PB Transition Coupling Kit
(Each kit contains 2 copper CrimpRings™ and one PB coupling)

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.

Dimensions – Weights

| MODEL | INLET | | | OUTLET | | | PKG. WEIGHT | |
|---|------------|-----------|---------------|------------|-----------|---------------|-------------|-------------|
| | <i>in.</i> | <i>mm</i> | <i>type</i> | <i>in.</i> | <i>mm</i> | <i>type</i> | <i>lbs.</i> | <i>kgs.</i> |
| PEX CrimpRing Couplings | | | | | | | | |
| WP15B-0606PB | 3/8 | 10 | Crimp Fitting | 3/8 | 10 | Crimp Fitting | 1 | 0.4 |
| WP15B-0806PB | 1/2 | 15 | Crimp Fitting | 3/8 | 10 | Crimp Fitting | 1 | 0.4 |
| WP15B-0808PB | 1/2 | 15 | Crimp Fitting | 1/2 | 15 | Crimp Fitting | 1 | 0.4 |
| WP15B-1208PB | 3/4 | 20 | Crimp Fitting | 1/2 | 15 | Crimp Fitting | 2 | 0.9 |
| WP15B-1212PB | 3/4 | 20 | Crimp Fitting | 3/4 | 20 | Crimp Fitting | 2 | 0.9 |
| WP15B-1612PB | 1 | 25 | Crimp Fitting | 3/4 | 20 | Crimp Fitting | 3 | 1.4 |
| WP15B-1616PB | 1 | 25 | Crimp Fitting | 1 | 25 | Crimp Fitting | 3 | 1.4 |
| WP15B-2020PB | 1 1/4 | 32 | Crimp Fitting | 1 1/4 | 32 | Crimp Fitting | 3 | 1.4 |
| WP15B-1620PB | 1 | 25 | Crimp Fitting | 1 1/4 | 32 | Crimp Fitting | 3 | 1.4 |
| PEX x PEX CinchClamp Coupling Kits | | | | | | | | |
| WP8S-6 | 3/8 | 10 | PEX | 3/8 | 10 | PEX | 1 | 0.4 |
| WP8S-8 | 1/2 | 15 | PEX | 1/2 | 15 | PEX | 1 | 0.4 |
| WP8S-14 | 3/4 | 20 | PEX | 3/4 | 20 | PEX | 1 | 0.4 |
| WP8S-16 | 1 | 25 | PEX | 1 | 25 | PEX | 1 | 0.4 |
| PEX x PEX CrimpRing Coupling Kits | | | | | | | | |
| WP16B-06 | 3/8 | 10 | PEX | 3/8 | 10 | PEX | 1 | 0.4 |
| WP16B-08 | 1/2 | 15 | PEX | 1/2 | 15 | PEX | 1 | 0.4 |
| WP16B-12 | 3/4 | 20 | PEX | 3/4 | 20 | PEX | 1 | 0.4 |
| WP16B-16 | 1 | 25 | PEX | 1 | 25 | PEX | 1 | 0.4 |
| WP16B-20 | 1 1/4 | 32 | PEX | 1 1/4 | 32 | PEX | 1 | 0.4 |
| PEX x PB Transition Coupling Kits | | | | | | | | |
| WP17B-06 | 3/8 | 10 | PEX | 3/8 | 10 | PB | 1 | 0.4 |
| WP17B-08 | 1/2 | 15 | PEX | 1/2 | 15 | PB | 1 | 0.4 |
| WP17B-12 | 3/4 | 20 | PEX | 3/4 | 20 | PB | 1 | 0.4 |
| WP17B-16 | 1 | 25 | PEX | 1 | 25 | PB | 1 | 0.4 |



WaterPEX Plumbing Products



ISO 9001-2000
CERTIFIED